

Package: XLS (via r-universe)

October 10, 2024

Imports mpoly

Title A Modeling Approach that Optimizes Future Errors in Least Squares

Version 0.1.0

Maintainer Samet Sokel <a_s@eskisehir.edu.tr>

Description Given the date column as an ascending entry, future errors are included in the sum of squares of error that should be minimized based on the number of steps and weights you determine. Thus, it is prevented that the variables affect each other's coefficients unrealistically.

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

Suggests rmarkdown, knitr

BugReports <https://github.com/sametsoekel/eXtreme-Least-Squares/issues>

Repository <https://sametsoekel.r-universe.dev>

RemoteUrl <https://github.com/sametsoekel/extreme-least-squares>

RemoteRef HEAD

RemoteSha 43d10dc78a9c66f2a3abc7f9003f7cf53a196ceb

Contents

xls.fit	2
xls.objfun	2
xls.prep	3

Index	4
--------------	----------

 xls.fit

Fitting an eXtreme Least Squares Model

Description

Almost the same interface as `stats::lm`. Just includes two parameters more, `error_weights` and `error_ahead_level`

Usage

```
xls.fit(formula, data, error_weights = NULL, error_ahead_level = 4)
```

Arguments

<code>formula</code>	An object of class "formula": a symbolic description of the model to be fitted.
<code>data</code>	A "data.frame" (with no missing values) object containing the variables in the model.
<code>error_weights</code>	A numeric vector including error weights by order. If NULL, it is created automatically by <code>error_ahead_level</code> amount, decreasing at equal intervals.
<code>error_ahead_level</code>	An integer which represents how many steps further the parameters will be optimized for each data point.

Value

A `lm` object whose coefficients are optimized by the mentioned method.

Examples

```
df <- datasets::airquality
ordered_df <- df[with(df, order(Month, Day)), ]
model <- xls.fit(Ozone ~ Solar.R + Wind + Temp, ordered_df,
  error_weights = c(0.4, 0.3, 0.2, 0.1), error_ahead_level = 4)
```

 xls.objfun

Preparing eXtreme Least Squares Nonlinear Objective Function

Description

Automatically used in `xls.fit()` No need to use if the objective function is not specifically desired to be achieved.

Usage

```
xls.objfun(data, error_column_name, error_weights, error_ahead_level)
```

Arguments

data A data.frame object which is returned by xls.prep. Tip: xls.prep's .data sub object returns the data.frame

error_column_name Symbolic error column's name. By default, it is named "error_symbolic" by xls.prep()

error_weights A numeric vector including error weights by order.

error_ahead_level An integer which represents how many steps further the parameters will be optimized for each data point.

Value

A function object.

xls.prep

Preparing eXtreme Least Squares Data

Description

Automatically used in xls.fit() No need to use if the raw data is not specifically desired to be achieved.

Usage

```
xls.prep(formula, data, dependent_var)
```

Arguments

formula An object of class "formula": a symbolic description of the model to be fitted.

data A data.frame object.

dependent_var A character which is the same as left hand side variable in specified formula.

Value

A list object which contains a data.frame object to be modeled and character vector of independent variables.

Index

`xls.fit`, 2
`xls.objfun`, 2
`xls.prep`, 3